



10/530691

CT/GB 2003 / 0 0 4 0 6 9



INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 0 6 NOV 2003

WIPO


PC

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

14 October 2003

BEST AVAILABLE COPY

Patents Form 1/77
 Pat (R) Act 1977
 11 OCT 2002
 NEWPORT



1/77
 11OCT02.E755187-4 002896
 P01/7700 0.00-0223683.4

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form).

The Patent Office

Cardiff Road
 Newport
 South Wales
 NP10 8QQ

1. Your reference

RAB.P04719GB

2. Patent application

(The Pat

0223683.4

11 OCT 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Haygrove Limited
 Redbank
 Ledbury
 Herefordshire HR8 2JL

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

8482366001

4. Title of the invention

Harvesting Apparatus

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Marks & Clerk
 27 Imperial Square
 Cheltenham
 Gloucestershire GL50 1RQ
 United Kingdom

Patents ADP number (if you know it)

18014

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
 (if you know it)

Date of filing
 (day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
 (day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d)

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description

~~9~~ 9 /

Claim(s)

~~4~~ 4 /

Abstract

1 /

Drawing(s)

2 + 2 A

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(*please specify*)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Mark & Cleve

Date 10.10.02

Agents for the Applicants

12. Name and daytime telephone number of person to contact in the United Kingdom

Richard A. Bailey - 01242 524520

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

HARVESTING APPARATUS

The present invention relates to harvesting apparatus for hand picking of field-grown produce and in particular, but not exclusively, to ground-level field-grown produce.

Harvesting apparatus on which a picker can sit or lie is known. The harvesting apparatus is moved along the rows of the field and the picker picks the produce as it is approached. The picked produce is placed in a suitable container for packing on a separate, independent machine or at a later date.

The problem with this type of apparatus is the irregularity of the produce. At some points along the rows, the produce may be sparse, while at other points there will be clusters. This entails the apparatus having to repeatedly adjust its speed or even stop and start.

A further problem then occurs when the apparatus is intended to support more than one picker to enable picking of produce from adjacent rows. In this case, it becomes increasingly problematic to adjust the speed of the harvesting apparatus to suit each picker.

Once the container in which the picked produce has been placed is full, the container must be emptied before further picking can take place. This entails halting the picking of the produce, which is undesirable.

A further disadvantage that has been recognised is the need for the full containers to be transferred to a separate packing station. Again, this results in wasted time and, as a consequence, is undesirable.

The present invention seeks to overcome these problems.

According to a first aspect of the present invention, there is provided harvesting apparatus for use when manually harvesting field-grown produce, the harvesting apparatus having a support structure, a plurality of driven rotatable members by which the support structure can be moved, and a body support element supported by the support structure, the body support element being able to support a picker, as hereinbefore defined, and being movable over an extended range relative to the support structure so that the body support element can be selectively positioned relative to the support structure.

10

Preferable and/or optional features of the first aspect of the present invention are set forth in claims 2 to 15, inclusive.

According to a second aspect of the present invention, there is provided a method of manually hand-picking produce arranged in rows using harvesting apparatus as claimed in any one of the preceding claims, the method comprising the steps of :

- a) a picker positioning him, or her, -self on a body support element of the harvesting apparatus;
- b) driving the harvesting apparatus along the rows of the produce; and
- c) the picker manually hand-picking the produce as it approaches, and selectively moving the body support element over the extended range to optimise the position of the picker relative to the occurrence of the produce, so that an increase in the amount of produce picked and an increase in the speed of movement of the harvesting apparatus can be obtained.

25

Preferable and/or optional features of the present invention are set forth in claims 17 to 19, inclusive.

30

According to a third aspect of the present invention, there is provided harvesting apparatus for use when manually harvesting field-grown produce, the harvesting apparatus having a support structure, a plurality of driven rotatable members by which the support structure can be moved, a plurality of body support elements supported by the support structure and on which pickers, as
5 hereinbefore defined, can be supported to harvest the said produce, a collection area at which the harvested produce is deposited, and a conveyor system which transports the harvested produce from the picker to the collection area.

10 The present invention will now be described, by way of example, with reference to the accompanying drawings, in which :

Figure 1 is a schematic front elevational view of one embodiment of harvesting apparatus, in use, in accordance with the first aspect of the present invention;

15

Figure 2 is a schematic top plan view of the harvesting apparatus;

Figure 3 is a schematic side elevational view of the harvesting apparatus;
and

20

Figure 4 is a schematic perspective view of the harvesting apparatus.

Referring to the drawings, there is shown harvesting apparatus 10 having a support structure 12 (only shown in part), a plurality of rotatable members 14,
25 such as wheels or endless caterpillar tracks, mounted on a chassis of the support structure 12, means (not shown) for driving the rotatable members 14, and a plurality of body support elements 16 supported by the support structure 12. A conveyor system 18 and a collection area 20 are also supported by the support structure 12.

30

The body support element 16 is an elongate padded bed or bench suitably formed to enable a first user 22 (herein referred to as a 'picker') to lie prone facedown thereon.

5 Each body support element 16 is mounted on a linear runner or pair of linear runners (not shown), fixedly supported on the support structure 12, so that the body support elements 16 are slidable relative to the support structure 12. There is thus an extended range of travel or movement, which is greater than that which would be achievable by simply flexing or bending the human body when
10 in a prone position, from one end of the runner(s) to the other. The extended range of movement is in the order of 1 metre, but may be more.

Motorised means (not shown) are provided so that, by operation of a switch (not shown), each body support element 16 can be individually and
15 selectively driven along its runner(s). The switch is typically a foot operated switch located at, or adjacent to, the rear of the body support element 16.

Each body support element 16 can be adjusted in a direction transverse to the longitudinal extent of the runner(s), so that the horizontal distance between
20 adjacent body support elements 16 can be changed.

Each body support element 16 can also be adjusted vertically to alter the spacing between the respective body support element 16 and the ground.

25 The horizontal and vertical adjustments are effected via a motorised or manually-operated mechanism (neither of which is shown).

The collection area 20 is supported above the body support elements 16 and offset rearwardly relative thereto. The collection area 20 has space to
30 accommodate a plurality of stacks of packing containers 24. The drive of the

rotatable members 14 may also be controlled from the collection area 20.

The conveyor system 18 includes an endless rigid, or substantially rigid, conveyor track 26 mounted on the support structure 12, so that a first run 28 of the conveyor track 26 passes adjacent to the fronts of the body support elements 16 and a second run 30 passes through or adjacent to the collection area 20. Receiving members, typically in the form of trays 32, are suspended from the conveyor track 26 and are drivable around the conveyor track 26 through any conventional driving mechanism (not shown). The suspended height of each tray 32 is such that it travels along the first run 28 in or substantially in the horizontal plane of the body support elements 16, and adjacent to the fronts of the body support elements 16. The second run 30 of the conveyor track 26 is arranged so that the trays 32 travel at a height to enable convenient access thereto by a second user 36 (herein referred to as a 'packer').

15

In use, the harvesting apparatus 10 is manoeuvred into position adjacent to a first set of rows 38 having produce to be picked, so that the rotatable members 14 align or substantially align with the troughs 40 of the rows 38. Each picker 22 horizontally adjusts his, or her, allocated body support element 16 to correspond to their allocated row and the pitch of the rows. Each picker 22 also vertically adjusts the body support element 16 to take account of their body size and arm length.

25

Each picker 22 then lies facedown on the body support element 16.

The packer 36 starts and controls the harvesting apparatus 10, so that it preferably moves down the rows at a constant or substantially constant speed. The conveyor system 18 is also started.

30

Due to the movement of the harvesting apparatus 10, each picker 22 picks

the produce in their row as it approaches. The picker 22 operates their sliding body support element 16, via their foot switch, to slide in a forwards or backwards direction relative to the support structure 12 of the harvesting apparatus 10. This has the effect of temporarily increasing or decreasing the speed of the picker 22 relative to the support structure 12, so that the picker 22 can optimise their position relative to the occurrence of the produce. Consequently, more produce can be reached, while a higher constant forward speed of the harvesting apparatus 10 can be maintained.

10 As the produce is picked, it is placed on a passing tray 32. The tray 32 passes around the conveyor track 26 to the collection area 20, where the produce is removed by the packer 36 and packed in one of the packing containers 24.

15 The collection area 20 includes a packing surface 37 which can be used for quality control of the picked produce, weighing the produce, and so forth.

When the harvesting apparatus 10 reaches the end of the first set of rows 38, it is manoeuvred into position adjacent a further set of rows (not shown) ready for the produce in these further rows to be picked.

20 Typically, the sets of rows are housed within individual growing tunnels (supporting ribs of which are referenced as 42 in the Figures), which provide an improved growing environment. In this case, the harvesting apparatus 10 is dimensioned to be able to move within the growing tunnel, and the number of body support elements 16 is a multiple of the number of rows housed therewithin.

Obviously, the speed of the harvesting apparatus can be altered as it is travelling along the rows, or the harvesting apparatus can indeed be halted at any point. The drive of the rotatable members could be controlled by a picker from

30

the body support element, for example.

In a modification to the invention, the body support elements could be manually slidable as opposed to being motorised.

5

Furthermore, the harvesting apparatus could be adapted to accommodate only a single slidable body support element for a single picker.

The slidable body support element could also be adjustable to enable a
10 picker to be selectively supported in a sitting position and a prone position.

Although the body support elements are slidable, they could be movable in any other suitable way, such as being swingable or pivotable, provided the extended range of movement, beyond that which is capable simply by flexation
15 or bending of the human body when in a prone position, is permitted.

Although the harvesting apparatus is mainly intended for use with the manual hand-picking of ground-level field-grown produce, such as strawberries, it could be adapted for use with other types of field-grown produce requiring
20 manual hand-picking.

The driving means may include feedback control for automatically adjusting the movement of the harvesting apparatus. For optimising the speed of movement, position sensors, or any other suitable alternative, can be included
25 which determine the position of the body support elements and which output signals to control circuitry whereby the driving means determines the optimum speed of the harvesting apparatus which allows the body support elements to remain as close to the centre of their respective runners as possible. Consequently, body support elements will not often be at the limits of their
30 runners.

Further sensors can be used to sense the gaps in between rows of produce and to output signals by which the driving means can automatically steer the harvesting apparatus. This allows pickers and packers to concentrate on the picking and packing of the produce, respectively.

The pickers may have one or more individual punnet containers carried in one hand, or removably supported by a holder (not shown) fixed to the body support element. Once the punnet container is suitably full, it can be placed on a passing tray for transportation to the collection area. Empty punnet containers are then placed on the passing trays for transportation back to the pickers.

The packing surface of the collection area can thus be used for putting lids on the punnet containers and/or labelling the punnet containers prior to packing.

15

Also, a GPS-type monitoring system may be provided as part of the harvesting apparatus. This will enable monitoring and recordal of an amount of produce picked, and consequently enable predictive forecasting of expected future produce amounts. For example, the packer at the collection area is provided with a GPS transmitting device. When a predetermined number of packing containers are filled, notification is sent via the GPS device. The resultant amount of produce between consecutive notifications can then be determined based on the distance travelled by the harvesting apparatus. Alternatively, each body support element may be provided with a switch which operates each time a load of produce, for example a punnet container, is moved onto the conveyor system. Yields from every row can thus be monitored.

The harvesting apparatus is intended to be a single independent unit based around a unitary support structure. However, the harvesting apparatus could be split into units which are interconnected and/or bridged, for example a body

30

support element unit and a collection area unit interconnected or bridged via the conveyor system.

5 By the provision of the body support elements with extended range of movement, it is thus possible to provide harvesting apparatus which can be driven along rows of produce at relative high speed while the position of the or each body support element, relative to the support structure of the harvesting apparatus, can be optimised based on the occurrence of produce to be picked.

10 The embodiments described above are given by way of example only, and modifications will be apparent to persons skilled in the art without departing from the scope of the invention as defined by the appended claims. For example, the horizontal and vertical adjustment of the body support element could be dispensed with; and the body support element could be movable over an
15 extended range in more than one direction.

CLAIMS

1. Harvesting apparatus for use when manually harvesting field-grown produce, the harvesting apparatus having a support structure, a plurality of driven
5 rotatable members by which the support structure can be moved, and a body support element supported by the support structure, the body support element being able to support a picker, as hereinbefore defined, and being movable over an extended range relative to the support structure so that, when the harvesting apparatus is moving in a first direction, the body support element can be
10- selectively positioned relative to the support structure.
2. Harvesting apparatus as claimed in claim 1, wherein a plurality of the movable body support elements is provided.
- 15 3. Harvesting apparatus as claimed in any one of the preceding claims, wherein the extended range of movement is in the order of 1 metre or more.
4. Harvesting apparatus as claimed in any one of the preceding claims, wherein the or each body support element includes motorised means for
20 adjusting the position of the body support element relative to the support structure.
5. Harvesting apparatus as claimed in any one of claims 1 to 3, wherein the or each body support element is manually movable.
25
6. Harvesting apparatus as claimed in any one of the preceding claims, wherein the or each body support element is slidable along a linear runner or pair of linear runners fixedly supported on the support structure.
- 30 7. Harvesting apparatus as claimed in any one of the preceding claims,

wherein the or each body support element is vertically adjustable relative to the support structure to suit an individual picker.

8. Harvesting apparatus as claimed in any one of the preceding claims,
5 wherein the or each body support element is adjustable in a transverse direction.

9. Harvesting apparatus as claimed in any one of the preceding claims,
wherein the or each body support element is adapted to enable the respective
picker to lie prone thereon.

10

10. Harvesting apparatus as claimed in any one of the preceding claims,
further comprising a conveyor system and a collection area, the conveyor system
transporting produce placed thereon by the picker to the collection area for
packing.

15

11. Harvesting apparatus as claimed in claim 10, wherein the conveyor system
includes an endless rigid track which is supported by the support structure and
from which receiving members are suspended.

20 12. Harvesting apparatus as claimed in claim 10 or claim 11, wherein the
collection area is supported by the support structure.

13. Harvesting apparatus as claimed in any one of the preceding claims,
further comprising means for optimising the speed of the driven rotatable
25 members based on the position of the or each body support element relative to
the support structure.

14. Harvesting apparatus as claimed in claim 13, wherein the speed
optimisation means includes one or more position sensors which monitor the
30 position of the or each body support element.

15. Harvesting apparatus as claimed in any one of the preceding claims, further comprising one or more sensors through which the direction of movement of the harvesting apparatus can be automatically adjusted.

5

16. A method of manually hand-picking produce arranged in rows using harvesting apparatus as claimed in any one of the preceding claims, the method comprising the steps of :

10 a) a picker positioning him, or her, -self on a body support element of the harvesting apparatus;

b) driving the harvesting apparatus along the rows of the produce at a constant or substantially constant speed; and

15

c) the picker manually hand-picking the produce as it approaches, and selectively moving the body support element over the extended range to optimise the position of the picker relative to the occurrence of the produce, so that an increase in the amount of produce picked and an increase in the speed of movement of the harvesting apparatus can be obtained.

20

17. A method as claimed in claim 16 when dependent on claim 7 or claim 8, further comprising a step (d), prior to step (a), of adjusting the relative vertical and/or transverse position(s) of the body support element to suit the picker.

25

18. A method as claimed in claim 16, when dependent on any one of claims 10 to 12, or claim 17, further comprising a step (e), subsequent to step (c), of placing the picked produce on the conveyor system.

30 19. A method as claimed in claim 18, further comprising a step (f),

subsequent to step (e), of a packer at the collection area removing the picked produce from the conveyor system and packing the picked produce.

20. Harvesting apparatus for use when manually harvesting field-grown
5 produce, the harvesting apparatus having a support structure, a plurality of driven
rotatable members by which the support structure can be moved, a plurality of
body support elements supported by the support structure and on which pickers,
as hereinbefore defined, can be supported to harvest the said produce, a
collection area at which the harvested produce is deposited, and a conveyor
10 system which transports the harvested produce from the picker to the collection
area.

21. Harvesting apparatus substantially as hereinbefore described with
reference to the accompanying drawings.

ABSTRACT

Harvesting apparatus 10 has a support structure 12, a plurality of driven rotatable members 14 by which the support structure 12 can be moved, and a body support element 16 supported by the support structure 12. The body support element 16 is able to support a picker 22 and is slidable relative to the support structure 12 so that, when the harvesting apparatus 10 is moving in a first direction, the body support element 16 can be selectively positioned relative to the support structure 12 to optimise the position of the picker 22 relative to the occurrence of produce to be picked. Preferably, a conveyor system 18 and collection area 20 are also included on the support structure 12. The conveyor system 18 enables transportation of produce placed thereon by the picker to the collection area 20 for packing. A method is also provided.

Fig. 1







Fig. 2





**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.